

Suction motor with step-less pressure adjustment

Re-chargeable battery with low battery indication

Resistant to corrosive sanitizing liquids

Utilizing original Japanese technology, portable sprayer MSB1500Li(Z) has been designed to combine ease of operation and reliability. Suction pump with adjustable pressure ensures consistent pressure throughout the entire job. Swing type tank with internal balancing filters offer comfort of carrying 15 liters capacity tank. Built-in re-chargeable battery offers trouble free movement of user without hassle of trailing power cord. Low battery LED indication alerts user to recharge battery. Cushion pads are provided on back of sprayer and on the straps for comfort of the user. Various plastic, rubber and stainless steel components of MSB1500Li(Z) have been chosen to resist corrosive liquids such as Sodium Hypo Chloride.

TECHNICAL SPECIFICATIONS

Tank capacity	15 liters
Tank material	Polyethylene resin
Power	Re-chargeable battery
Battery type	Lithium-ion 18V. 3.0Ah
Charging time	60 minutes
Continuous running time	40~300 minutes
Suction volume	1.5 L/min
Max. pressure	1.0MPa
Nozzle	2-head
Dimension	250 x 370 x 550mm
Dry weight	5.3 kgs.



using anti-corrosive parts



arge filter for balance inside tank



2-head nozzle

Nozzle heads are made up mainly of

resin to support light weight design

of the sprayer. Only those parts which are essential to produce mist are made up of stainless steel.

adjustment knob



Measuring cup provided



BATTERY

LED battery level indicator



Cushion pads

DUE TO CONTINUOUS PRODUCT IMPROVEMENT, THE DESIGN AND TECHNICAL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

TASHIKA CO., LTD.

1-12, Kaiyo-cho, Ashiya, 659-0035, JAPAN Tel: + 81-797-23-9035 Fax: + 81-797-23-2105 e-mail: sales@tashika.co.jp URL: www.tashika.co.jp